



1000111010101100100011110001000001111000100

digital perfection



Mobile Thermal Printer

DPP-350





1000111010101100100011110001000001111000100

digital perfection



Specification



| | |
|------------------------------------|---|
| DPP-350 | |
| Printing Method | Line Thermal Printing |
| Total Dots | 576 dots / line |
| Dot Density | 8 dots / mm (203 dpi) |
| Print Speed | 60 mm / sec |
| Print Width Characters per Line | 72 mm Font A: 48 characters / line Font B: 64 characters / line Font C: 48 characters / line (loadable) Font D: 64 characters / line (loadable) |
| Recommended Paper | <ul style="list-style-type: none"> Thermal Paper Roll: <ul style="list-style-type: none"> - 78 mm / Ø 50 mm, thickness 60 µm; - 80 mm / Ø 50 mm, thickness 60 µm; - 57 mm / Ø 50 mm, thickness 60 µm. Label Paper Roll: <ul style="list-style-type: none"> - 78 mm / Ø 50 mm; - 57 mm / Ø 50 mm. |
| Interfaces | <ul style="list-style-type: none"> • RS-232C with optional special cable (1200 – 115200 bps); • USB 1.1 compatible 2.0 host / slave; • Bluetooth (option); • Wi-Fi (option). |
| Drivers for | <ul style="list-style-type: none"> • Pocket PC; • Palm OS; • Windows; • BlackBerry. |
| Configuration options | <ul style="list-style-type: none"> • Magnetic Stripe Reader (option); • Smart Card Reader (option); • Mi FARE Reader (option); • SD Card Slot for SD Card or Wi-Fi Modules (option). |
| Emulation | ESC/POS / LABEL <ul style="list-style-type: none"> • Label Printing ELTRON compatible (EPL-2); label length 100 mm maximum; • Barcode Printing: EAN13, EAN8, UPC-A, UPC-E, Codabar, Code 39, Code 128. |
| Power Supply | Rechargeable battery (Li-Ion 7.4V; 2000 mAh) |
| Battery Charge Time | 3 hours maximum |
| Print Lines per Charge | 30,000 (fully charged) |
| Buffer | <ul style="list-style-type: none"> • ESC/POS mode: 56 Kb; • Label mode: 16 Kb. |
| Reliability | 50,000,000 pulses or 50 km mechanism (MCFB): 15,000,000 lines |
| Weight | 340 grams (w / o paper); 430 grams (with paper); 540 grams (with label paper roll). |
| Dimension (w) x (d) x (h), mm | 108 x 111 x 62 |
| Environment | <ul style="list-style-type: none"> • Operating -10°C to +50°C • Storage -20°C to +60°C |
| More features / Applications | <ul style="list-style-type: none"> • Mobile; • Traveling sales; • Retail; • Transportation; • Receipt Printer; • Point of sales; • Healthcare; • Warehousing; • Distribution. |
| Accessories | <ul style="list-style-type: none"> • Wearable built-in metal belt hook • Neck / shoulder lanyard |



DATECS

115 A Tsarigradsko shosse Blvd., Sofia 1784, BULGARIA
tel: +359 (2) 974 00 55; fax: +359 (2) 974 11 00; e-mail: sales@datecs.bg; www.datecs.bg

001