

CGPrint

portable/desktop printer series

Portable or Desktop: The CGPrint series may be used as a desktop/wall-hung unit or as a hand-held/belt-hung, battery-operated unit to meet a wide variety of needs. It is ideal for EFT (electronic fund transfer) and POS (point of sales) transactions, in-the-field receipting and other applications that require a small foot print and/or portability. It also offers in-vehicle receipting for taxi and other public transportation provides.



Impact or thermal: The CGPrint series also offers a choice of printing technologies. Impact dot matrix and direct line thermal option are available.

Wide interface range: The CGPrint series also offer for RS-232C serial interface, Serial TTL interface, and Infrared communication interface (IrDA)

Paper end detector

**Portable
and/or Desktop
applications**

Text and graphics mode

**Impact or thermal
print option**

OEM version available

**RS-232C, TTL
serial or IrDA
interface**

Customised case colours


**57 mm wide
paper**

CGP RINTE

specification and type classification

DPP-40/R 230 A13 B 32K

1 2 3 4 5



Series

Paper width	57mm + - 0.5mm
Paper roll diameter	50mm
Buffer	1 line
Dimension (W x D x H)	105x150x75
Case colours	anthracite grey / indigo blue / beige



1 Model type

Printing method	impact dot matrix	Direct line thermal
Printer mechanism	MD-900 series (Citizen)	LT-286 (Citizen)
Paper end detector	optional	Yes
Ink ribbon cassette	IR-91 (black or purple)	-
Operating temperature range	0 - 50 C	-10 - 50C

DP:dot matrix

TP:line thermal

Rechargeable battery
Power source

D:desktop

P:portable

-	NiCd 700mAh
DC 12V 800mA	DC 12V 500mA

2 Columns

Text mode	24 char/line	40 char/line	24 (line thermal) 24 char/line	42 (line thermal) 42 char/line
Graphics mode	144 dots/line	180 dots/line	384 dots/line	384 dots/line
Printing speed	2.5 line/sec	1.8 line/sec	6 line/sec	4 line/sec

24 (dot matrix)

40 (dot matrix)

24 (line thermal)

42 (line thermal)

3 Interface

R	T	I
RS-232	TTL serial	IrDA (V1.1) + RS-232

4 Power supply

Power supply	AC 120V	230 AC 230V	240 AC 240V
Wall adapter type	USA plug	European plug	UK plug

120


230

240

5 Optional

+A13	+32K	+B
NiMH 1300mAh battery	32K buffer	Belt adapter

Manufacturer:

 **CGP Electronics Ltd.**

H-2220 Vecsés Küküllői utca 33. Hungary
Tel: +36 (20) 93 48 956
Fax: +36 (29) 351-990
E-mail: sales@cgp.hu Web: www.cgp.hu

Your distributor: